

A 5153027

HEAT TREATMENT & FINAL FINISH			PHYSICAL PROPERTIES			REVISIONS	
Y.P.	RED	ROCK					
T.S.	BR.						
EL 2							
DIAMETER OF WIRE041 TOTAL NUMBER OF COILS 6 1/2 MINIMUM INSIDE DIAMETER, FREE 268 OUTSIDE DIAMETER, FREE 35+ .01 MAXIMUM OUTSIDE DIAMETER AT MINIMUM OPERATING HEIGHT 364 FREE LENGTH OF SPRING 82+ .01 TYPE OF ENDS PLAIN WOUND R.H. MEAN ASSEMBLED HEIGHT 44 LOAD AT MEAN ASSEMBLED HEIGHT 9.2 LBS. MINIMUM OPERATING HEIGHT 34 LOAD AT MINIMUM OPERATING HEIGHT 12.2 LBS. SPRING FUNCTIONS IN HOLE 375+ .005 CALCULATED MAXIMUM SOLID HEIGHT 31			DRG. PERTAINS TO 51-63 .45 SMG-M28A1 51-116 .45 SMG-M1 51-124 .45 SMG-M1A1			1' 9-30-42 2 CONVERSION 10-17-51	
NOTE:- EXPAND LAST COIL ON ONE END TO OUTSIDE DIA. OF .39+ .01			SPRING, TRIGGER 5153027 5153027			DECEMBER 31, 1941	

SUPERSEDES A 55027

NOTE:- EXPAND LAST COIL ON ONE END
TO OUTSIDE DIA. OF .39+ .01

SPRING, TRIGGER (5153027-5153027)